



# ELO Hydraulic Valve Components Co., ...

## 110 mm x 170 mm x 28 mm NSK NU1022 JAPAN Bearing

Bearing No. NU1022



NU1022 Bearing 2D drawings and 3D CAD models

Bore Diameter	110 mm
Outer Diameter	155 mm
d	110 mm
Fw	125 mm
D	170 mm
Ew	155 mm
B	28 mm
C	28 mm
r min.	2 mm
r1 min.	1,1 mm
da min.	119 mm
ra max.	2 mm
rb max.	1 mm
Weight	2,27 Kg
Basic dynamic load rating (C)	131 kN
Basic static load rating (C0)	174 kN
(Grease) Lubrication Speed	3 800 r/min
hidYobi	NU1022
LangID	1
D_	170
B_	28
hidTable	ecat_NSCLDR
Oil rpm	4500
rb	1
mass	2.27



## ELO Hydraulic Valve Components Co., ...

GRS rpm	3800
ra	2
db max	123
TSR rpm	4500
C0	174
DE_	155
Prod_Type3	CRB_SR_NU
da	119
DA_	15
Z_	22
D_a max	161
yobi	NU1022
C_conv	131000
ALPHA_	0
SDM_	140
r	2
db min	116.5
dc min	128
KBRG	4144
SBRG	10
r1	1.1
DI_	125